


3000 SERIES SYSTEM POWER SUPPLY

直流电源供应器



- 型号 **33010D** (CE)
DC 30V/10A
- 型号 **3303D** (CE)
DC 30V/3A

Ordering Information:



CE / GS
EMC/Safety Requirement
Remote Control / Sensing
Digital Display
Current : 3A
Voltage : 30V
3000 Series

- 2 built-In Analog / Digital Display
- Constant voltage / Current
- Series / Parallel Available
- Short circuit / External Input Protection
- Compact Size

Model	Dimension	Model Type					
3203	S	A	D	AR	DR	AS*	DS*
3302	S	A	D	AR	DR	AS*	DS*
3303	S	A	D	AR	DR	AS*	DS*
3601	S	A	D	AR	DR	AS*	DS*
3306	L	/	D	/	DR	/	/
3603	L	/	D	/	DR	/	/
33010	L	/	D	/	DR	/	/

Dimension S size: 120 (W) x 160 (H) x 295 (D)

Dimension L size: 230 (W) x 160 (H) x 366 (D)

* Models with CE/GS Marks

Net Weight : (3203, 3302, 3303, 3601) ≈ 5.5kg

Net Weight : (3306, 3603) ≈ 9.5kg

Net Weight : (33010) ≈ 14.0kg

1310 DIGITAL WATT AMMETER

功率表



Specification

Range 19.99W, 199.9W, 1999W

Accuracy ±(0.3% +3d)

Power Factor 0 ~ 1

- Dual display digital V-A-M
- True Watt & True RMS Current

5030 LCR METER

电感、电容、电阻测试器



Specification

Accuracy ±0.2%

Test Frequency 100Hz, 120Hz, 1KHz, 10KHz

Test Mode Auto / Manual

L: 0.001μF ~ 9999H, C: 0.001pF ~ 9999mF

Display Range R: 0.001 Ω ~ 999M Ω, D: 0.001 ~ 9999

Q: 0.001 ~ 9999

TPT-500 SERIES PUNCTURE / INSULATION TESTER 漏电测试器



500A (AC Only)



500ADT (AC, DC & Timer)



500AT (AC & Timer)

- Puncture & Insulation test by same terminal
- Two ranges for Insulation 500M Ω / 1000M Ω
- Remote control on test probe
- 0~5KV continuously variable
- Cut-Off current 0.1, 0.5, 1, 3, 5, 10mA with variable adjustment