

“Globe” Brand, Digital Ammeter and Digital Voltmeters. Injection moulded in a robust plastic case, these digital ammeter and digital voltmeter feature inherent strength and resilience coupled with attractive, modern styling and practicality. The liquid crystal display has 13mm high digits and features an indication of polarity and low-battery. The display has a wide field of view unobscured by trailing leads. Two colour - coded 4mm sockets, battery included.

The units are designed to withstand rigorous use and will survive impact with the floor should they be accidentally knocked off a bench.

Each meter has an accuracy of +/- 0.1% of full scale, +/- 1 digit.

Digital Voltmeters

	<u>Model PA-201</u>	<u>Model PA-202</u>
Description	20V d.c. Voltmeter	2V d.c. Voltmeter
Range	0-19.99V d.c.	0-1.999V d.c.
Resolution	10mV	1mV
Input resistance	10M Ω [10M Ω [
Electrical supply	----- Battery, 9V, 6LR61 (PP3) type ---	
Dimensions, mm	----- 140 x 100 x 90 -----	



PA-201 & PA-202



PA-211 & PA-212

Digital Ammeters

	<u>Model PA-211</u>	<u>Model PA-212</u>
Description	10A Ammeter	2A Ammeter
Range	0-10.00A d.c.	0-1.999A d.c.
Resolution	0.01A	1mA
Overload	2 x full scale	fused
Input resistance	0.01 Ω [0.1 Ω [
Electrical supply	--- Battery, 9V, 6LR61 (PP3) type --	
Dimensions, mm	----- 140 x 100 x 90 -----	

Digital Ammeters

	<u>Model PA-213</u>	<u>Model PA-214</u>
Description	Milliammeter	Microammeter
Range	0-199.9mA d.c.	0-199.9 μ A d.c.
Resolution	0.1mA	0.1 μ A
Overload	fused	10 x full scale
Input resistance	1 Ω [1000 Ω [
Electrical supply	----- Battery, 9V, 6LR61 (PP3) type ---	
Dimensions, mm	----- 140 x 100 x 90 -----	



PA-213 & PA-214